



DYNALOIL ZINC RICH 27301 - Código - 21902

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** DYNALOIL ZINC RICH 27301 - Código - 21902
Other means of identification:
UFI: HFU0-S0V7-S00V-JA2H
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Primers and hardening base layers.. For professional users/industrial user only.
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 INDUSTRIAS JUNO, S.A.
 Barrio Sakoni, 10
 48950 ERANDIO - Vizcaya - España
 Phone: +34 944 670 062 - Fax: +34 944 675 832
 laboratorio@juno.es
 www.juno.es
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
 Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410
 Flam. Liq. 3: Flammable liquids, Category 3, H226
 Lact.: Reproductive toxicity, effects on or via lactation, H362

- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled.
 Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Lact.: H362 - May cause harm to breast-fed children.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313: IF exposed or concerned: Get medical advice/attention.
 P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.
 P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide). May produce an allergic reaction.

Substances that contribute to the classification

Reaction mass of ethylbenzene and m-xylene and p-xylene; Alkanes, C14-17, chloro (CAS: 85535-85-9)

UFI: HFU0-S0V7-S00V-JA2H

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 7440-66-6 EC: 231-175-3 Index: 030-002-00-7 REACH: 01-2119467174-37-XXXX	Zinc powder - zinc dust (stabilised)⁽¹⁾ ATP CLP00 Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	50 - <75 %
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16-XXXX	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7⁽¹⁾ ATP ATP01 Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	2,5 - <10 %
CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-211955267-33-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	2,5 - <10 %
CAS: 1314-13-2 EC: 215-222-5 Index: 030-013-00-7 REACH: 01-2119463881-32-XXXX	zinc oxide⁽¹⁾ ATP CLP00 Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	2,5 - <10 %
CAS: 85535-85-9 EC: 287-477-0 Index: 602-095-00-X REACH: 01-2119519269-33-XXXX	Alkanes, C14-17, chloro⁽¹⁾ ATP ATP01 Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362; EUH066 - Warning	<1 %
CAS: Non-applicable EC: 430-050-2 Index: 616-127-00-5 REACH: 01-2120789217-43-XXXX	Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide)⁽¹⁾ ATP CLP00 Regulation 1272/2008 Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	<1 %
CAS: 108-95-2 EC: 203-632-7 Index: 604-001-00-2 REACH: 01-2119471329-32-XXXX	phenol⁽²⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: H373 - Danger	<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
phenol CAS: 108-95-2 EC: 203-632-7	% (w/w) >=3: Skin Corr. 1B - H314 1<= % (w/w) <3: Skin Irrit. 2 - H315 % (w/w) >=1: Eye Irrit. 2 - H319

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity	Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral Not relevant	
CAS: Non-applicable	LD50 dermal 1100 mg/kg	Rat
EC: 905-562-9	LC50 inhalation 11 mg/L (ATEI)	

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
phenol	100 mg/kg	630 mg/kg	Rat
CAS: 108-95-2			Rabbit
EC: 203-632-7	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C
 Maximum Temp.: 30 °C
 Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	50 ppm	221 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene	IOELV (STEL)	100 ppm	442 mg/m ³
CAS: Non-applicable EC: 905-562-9	IOELV (8h)	2 ppm	8 mg/m ³
phenol ⁽¹⁾	IOELV (STEL)	4 ppm	16 mg/m ³
CAS: 108-95-2 EC: 203-632-7			

⁽¹⁾ Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	5 mg/m ³	Not relevant
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Not relevant	837,5 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	5 mg/m ³	0,5 mg/m ³
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	47,9 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	6,7 mg/m ³	Not relevant
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxodecyl]amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	17,62 mg/m ³	Not relevant
phenol CAS: 108-95-2 EC: 203-632-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1,23 mg/kg	Not relevant
	Inhalation	Not relevant	16 mg/m ³	8 mg/m ³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2,5 mg/m ³	Not relevant
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	1152 mg/m ³	640 mg/m ³	Not relevant	178,57 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2,5 mg/m ³	Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	Oral	Not relevant	Not relevant	0,58 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	28,75 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	2 mg/m ³	Not relevant
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2	Oral	Not relevant	Not relevant	2,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	Not relevant
phenol CAS: 108-95-2 EC: 203-632-7	Oral	Not relevant	Not relevant	0,4 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,4 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	1,32 mg/m ³	Not relevant

PNEC:

Identification				
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	STP	0,1 mg/L	Fresh water	0,0206 mg/L
	Soil	106,8 mg/kg	Marine water	0,0061 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	235,6 mg/kg
	Oral	Not relevant	Sediment (Marine water)	121 mg/kg
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
zinc oxide CAS: 1314-13-2 EC: 215-222-5	STP	0,1 mg/L	Fresh water	0,0206 mg/L
	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	117,8 mg/kg
	Oral	Not relevant	Sediment (Marine water)	56,5 mg/kg
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	STP	80 mg/L	Fresh water	0,001 mg/L
	Soil	11,9 mg/kg	Marine water	0,0002 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	13 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	2,6 mg/kg
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2	STP	100 mg/L	Fresh water	0,000058 mg/L
	Soil	1 mg/kg	Marine water	0,000006 mg/L
	Intermittent	0,000054 mg/L	Sediment (Fresh water)	1 mg/kg
	Oral	0,0333 g/kg	Sediment (Marine water)	0,1 mg/kg
phenol CAS: 108-95-2 EC: 203-632-7	STP	2,1 mg/L	Fresh water	0,008 mg/L
	Soil	0,136 mg/kg	Marine water	0,001 mg/L
	Intermittent	0,031 mg/L	Sediment (Fresh water)	0,091 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,009 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	 CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks	 CAT I		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	 CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	 CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	13,41 % weight
V.O.C. density at 20 °C:	371,82 kg/m ³ (371,82 g/L)
Average carbon number:	8,56
Average molecular weight:	119,5 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	371,82 kg/m ³ (371,82 g/L)
EU limit for the product (Cat. A.I):	500 g/L (2010)
Components:	Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	 Grey
Odour:	Solvent
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	143 °C
Vapour pressure at 20 °C:	642 Pa
Vapour pressure at 50 °C:	3574,4 Pa (3,57 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	2773,6 kg/m ³
Relative density at 20 °C:	2,774
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Soluble in organic solvents
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	24 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	200 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



DYNALOIL ZINC RICH 27301 - Código - 21902

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Surface tension at 20 °C: Not relevant *
 Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); phenol (3); Alkanes, C14-17, chloro (2B); Zeolites (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: May cause harm to breast-fed children

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (ATEi)	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation		
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LD50 oral	7950 mg/kg	Mouse
	LD50 dermal		
	LC50 inhalation		
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl) amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2	LD50 oral	5100 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation		
phenol CAS: 108-95-2 EC: 203-632-7	LD50 oral	100 mg/kg	Rat
	LD50 dermal	630 mg/kg	Rabbit
	LC50 inhalation		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	LC50	0,31 mg/L (96 h)	N/A	Fish
	EC50	1,22 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LC50	0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3,4 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
Alkanes, C14-17, chloro CAS: 85535-85-9 EC: 287-477-0	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxodecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
phenol CAS: 108-95-2 EC: 203-632-7	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	NOEC	0,44 mg/L	Oncorhynchus mykiss	Fish
	NOEC	0,031 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
zinc oxide CAS: 1314-13-2 EC: 215-222-5	NOEC	0,44 mg/L	Oncorhynchus mykiss	Fish
	NOEC	0,031 mg/L	Daphnia magna	Crustacean
phenol CAS: 108-95-2 EC: 203-632-7	NOEC	0,077 mg/L	Cirrhina mrigala	Fish
	NOEC	0,16 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	89,9 %
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
phenol CAS: 108-95-2 EC: 203-632-7	BOD5	1,68 g O2/g	Concentration	100 mg/L
	COD	2,33 g O2/g	Period	14 days
	BOD5/COD	0,72	% Biodegradable	85 %

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Substance-specific information:

Identification	Bioaccumulation potential	
Reaction mass of ethylbenzene and m-xylene and p-xylene	BCF	9
CAS: Non-applicable	Pow Log	2.77
EC: 905-562-9	Potential	Low
phenol	BCF	17
CAS: 108-95-2	Pow Log	1.48
EC: 203-632-7	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Koc	100	Henry	Not relevant
	Conclusion	High	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes
phenol CAS: 108-95-2 EC: 203-632-7	Koc	50	Henry	2,2E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	1,847E-2 N/m (231,01 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Alkanes, C14-17, chloro

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): *Alkanes, C14-17, chloro (85535-85-9)*
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

- H410: Very toxic to aquatic life with long lasting effects.
- H362: May cause harm to breast-fed children.
- H400: Very toxic to aquatic life.
- H332: Harmful if inhaled.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Lact.: H362 - May cause harm to breast-fed children.
- Muta. 2: H341 - Suspected of causing genetic defects.
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
- STOT SE 3: H335 - May cause respiratory irritation.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Aquatic Chronic 1: Calculation method
 Lact.: Calculation method
 Aquatic Acute 1: Calculation method
 Acute Tox. 4: Calculation method
 Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -