

**JUNO**

INDUSTRIA

# POXENAMEL 2/C

## Anti-corrosive range



2K Anti-corrosive polyurethane coatings (Poxenamel and Poxenamel HB). Formulated based on polyester resins and zinc-phosphate as corrosion inhibiting pigment.

### Recommended for:

As a primer and/or finish for direct application on metal, where good chemical and weather resistance is required, leaving a smooth, semi-gloss finish.

**Use:** Interior & Exterior

### Product features

- ✓ Excellent adhesion on steel and galvanized surfaces
- ✓ Excellent hardness
- ✓ Great opacity\*
- ✓ A la carte colours with JUNO's Industrial Tinting System

### Innovation



- ✓ Self-priming topcoat or as primer
- ✓ Achieve **ISO 12944** certification with a single product application



### Benefits of using 1 product system

- ✓ **Improves productivity** → Reduce application time
- ✓ **Improves profitability** → Reduce man-hours and application time
- ✓ **Eliminate primer cost** → Product is self-priming and can be used as primer and/or topcoat

### Certifications

Certified by the **EN ISO 12944** standard on anticorrosive systems. The certification regulates an expected durability with adequate maintenance between 15 and 25 years depending on the system used and microns applied.

**C3**

HIGH

**C4**

HIGH

**C5**

HIGH

\*Opacity in colours formulated with organic pigments may vary.

**JUNO****INDUSTRIA****POXENAMEL 2/C****POXENAMEL HB 2/C**

Semi-gloss	<b>Finish</b>	Semi-gloss
D-17 o D-71	<b>Thinner</b>	D-17 o D-71
White Base (P) (Prod.Ref. 08480), Deep Base (TR) (Prod.Ref. 08481) + Colours on demand	<b>Colours</b>	White Base (P) (Prod.Ref. 08430), Deep Base (TR) (Prod.Ref. 08431) + Colours on demand
7,2 m <sup>2</sup> /L	<b>Practical coverage</b>	8,3 m <sup>2</sup> /L
140 microns	<b>Thickness</b>	140 microns
4 hours @ 20° C	<b>Potlife</b>	2 hours @ 20° C
Brush, roller or sprayed	<b>Application method</b>	Brush, roller or sprayed
58% ± 2% (theoretical)	<b>Volume solids</b>	67% ± 2% (theoretical)
Valid as complete system (self-priming topcoat)	<b>Primer + Finish</b>	Valid as complete system (self-priming topcoat)
15 & 4 Litres	<b>Can size</b>	15 & 4 Litres

**JUNO INDUSTRIAL**

Barrio Urioste, 64 · 48530 Ortuella (Vizcaya) - SPAIN

Tel. + 34 944 17 5373

[export@juno.es](mailto:export@juno.es)

[www.junoindustria.es](http://www.junoindustria.es)  
[www.junopaints.com](http://www.junopaints.com)