

IMPRIMACION MULTISOPORTE BLANCA - Código - 27040



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Anticorrosion primer

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A. Barrio Sakoni, 10 48950 ERANDIO - Vizcaya - España Phone: +34 944 670 062 - Fax: +34 944 675 832 laboratorio@juno.es www.iuno.es

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

Contains Cobalt bis(2-ethylhexanoate), Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl) amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide), Rosin. EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

** Changes with regards to the previous version





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Xylene (CAS: 1330-20-7); Reaction mass of ethylbenzene and m-xylene and p-xylene ; Ethylbenzene (CAS: 100-41-4); Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine **Acute Toxicity Estimate (ATE mix):**

49,63 % (dermal), 82,18 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

UFI: 2300-D0YC-R00X-GH5Q

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of aggregates and pigments in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	ication Chemical name/Classification						
CAS:	64742-95-6	Solvent naphtha (pe	etroleum), light arom., < 0.1 % EC 200-753-7(1)	ATP ATP01				
EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24- XXXX		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger					
CAS:	1330-20-7	Xylene ⁽¹⁾		ATP CLP00				
EC: Index: REACH:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	(1) (1)	1 - <10 %			
CAS:	Non-applicable	Reaction mass of et	hylbenzene and m-xylene and p-xylene (1)	Self-classified				
EC: Index: REACH:	905-562-9 Non-applicable 01-2119555267-33- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger					
CAS:	7779-90-0			ATP CLP00				
	231-944-3 Non-applicable 01-2119485044-40- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	Ł	1 - <10 %			
CAS:	100-41-4	Ethylbenzene ⁽¹⁾ Self-classified						
	202-849-4 601-023-00-4 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	1 - <10 %			
CAS:	8050-09-7	Rosin ⁽¹⁾		ATP CLP00				
	232-475-7 550-015-00-7 01-2119480418-32- XXXX Regulation 1272	Regulation 1272/2008	Skin Sens. 1: H317 - Warning	٩	1 - <10 %			
CAS: Non-applicable EC: 430-050-2 Index: 616-127-00-5			N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1- yl]octadecanamide/N,N-Ethane-1,2-diylbis(12- mide) ⁽¹⁾	ATP CLP00				
REACH:	01-2120789217-43- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	<u>(!)</u>	0,1 - <1 %			
CAS:	108-88-3							
	203-625-9 601-021-00-3 : 01-2119471310-51- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	() (d) (d)	0,1 - <1 %			

⁽²⁾ Substance with a Union workplace exposure limit

- CONTINUED ON NEXT PAGE -





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification		Concentration	
CAS:	22464-99-9	2-ethylhexanoic acid	l, zirconium salt ⁽¹⁾	Self-classified	0,1 - <1 %	
EC: 245-018-1 Index: Non-applicable REACH: 01-2119979088-21 XXXX		Regulation 1272/2008	ulation 1272/2008 Repr. 2: H361d - Warning			
CAS: Non-applicable EC: 942-330-6			f Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, 5, compds. with oleylamine ⁽¹⁾	Self-classified		
REACH:	Non-applicable 01-2120101675-63- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1A: H317; STOT RE 2: H373 - Warning	(!)	0,1 - <1 %	
CAS:	136-52-7	Cobalt bis(2-ethylhexanoate) ⁽¹⁾ Self-classified				
EC: Index: REACH:	205-250-6 Non-applicable 01-2119524678-29- XXXX	on-applicable -2119524678-29- Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger	(Ì) 🚯 🏝	<0,1 %	
CAS:	112-34-5	2-(2-butoxyethoxy)ethanol ⁽²⁾ ATP CLP00		ATP CLP00		
Index: REACH:	203-961-6 603-096-00-8 01-2119475104-44- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	()	<0,1 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

(2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

- CONTINUED ON NEXT PAGE -

Date of compilation: 15/01/2013 Rev





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 5: FIREFIGHTING MEASURES (continued)

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 7: HANDLING AND STORAGE (continued)

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification		Occupational exposure limits		
Xylene		IOELV (8h)	50 ppm	221 mg/m ³	
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m ³	
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m ³	
CAS: 100-41-4	EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m ³	
Toluene		IOELV (8h)	50 ppm	192 mg/m ³	
CAS: 108-88-3	EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m ³	
2-(2-butoxyethoxy	2-(2-butoxyethoxy)ethanol		10 ppm	67,5 mg/m ³	
CAS: 112-34-5	EC: 203-961-6	IOELV (STEL)	15 ppm	101,2 mg/m ³	

DNEL (Workers):

		Short e	exposure	Long e	exposure
Identification		Systemic	Local	Systemic	Local
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200 -753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-95-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-199-0	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 905-562-9	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Rosin	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 8050-09-7	Dermal	Non-applicable	Non-applicable	2,131 mg/kg	Non-applicable
EC: 232-475-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	10 mg/m ³

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12- Hydroxy-N-[2-[1-oxydecyl)amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12- hydroxyoctadecanamide)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
EC: 430-050-2	Inhalation	Non-applicable	Non-applicable	17,62 mg/m ³	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	6,49 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	32,97 mg/m ³	Non-applicable
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,43 mg/kg	Non-applicable
EC: 942-330-6	Inhalation	Non-applicable	Non-applicable	0,75 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m ³
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³

DNEL (General population):

		Short e	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200 -753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-95-6	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-199-0	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Reaction mass of ethylbenzene and m-xylene and p-xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 905-562-9	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m ³	Non-applicable
Ethylbenzene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Rosin	Oral	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
CAS: 8050-09-7	Dermal	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
EC: 232-475-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12- Hydroxy-N-[2-[1-oxydecyl)amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12- hydroxyoctadecanamide)	Oral	Non-applicable	Non-applicable	2,5 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 430-050-2	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	4,51 mg/kg	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	3,25 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	8,13 mg/m ³	Non-applicable
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine	Oral	Non-applicable	Non-applicable	0,11 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,21 mg/kg	Non-applicable
EC: 942-330-6	Inhalation	Non-applicable	Non-applicable	0,37 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	0,175 mg/kg	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m ³
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	60,7 mg/m ³	40,5 mg/m ³	40,5 mg/m ³

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Reaction mass of ethylbenzene and m-xylene and p-xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: Non-applicable	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 905-562-9	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Rosin	STP	1000 mg/L	Fresh water	0,002 mg/L
CAS: 8050-09-7	Soil	0 mg/kg	Marine water	0 mg/L
EC: 232-475-7	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,007 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,001 mg/kg
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12- Hydroxy-N-[2-[1-oxydecyl)amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12- hydroxyoctadecanamide)	STP	100 mg/L	Fresh water	0,000058 mg/L
CAS: Non-applicable	Soil	1 mg/kg	Marine water	0,000006 mg/L
EC: 430-050-2	Intermittent	0,000054 mg/L	Sediment (Fresh water)	1 mg/kg
	Oral	0,0333 g/kg	Sediment (Marine water)	0,1 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
Reaction products of Fatty acids, tall-oil, compds. with oleylamine and Fatty acids, C18-unsatd., trimers, compds. with oleylamine	STP	100 mg/L	Fresh water	0,194 mg/L
CAS: Non-applicable	Soil	120 mg/kg	Marine water	0,019 mg/L
EC: 942-330-6	Intermittent	0,097 mg/L	Sediment (Fresh water)	29,6 mg/kg
	Oral	0,000416 g/kg	Sediment (Marine water)	2,96 mg/kg

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Cobalt bis(2-ethylhexanoate)	STP	0,37 mg/L	Fresh water	0,00062 mg/L
CAS: 136-52-7	Soil	10,9 mg/kg	Marine water	0,00236 mg/L
EC: 205-250-6	Intermittent	Non-applicable	Sediment (Fresh water)	53,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	69,8 mg/kg
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1,1 mg/L
CAS: 112-34-5	Soil	0,32 mg/kg	Marine water	0,11 mg/L
EC: 203-961-6	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure Standards Emergency measure Standards <u>_</u>+ ANSI Z358-1 DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 ISO 3864-1:2011, ISO 3864-4:2011 Emergency shower Eyewash stations **Environmental exposure controls:** In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: 31,07 % weight V.O.C. (Supply): 450,52 kg/m³ (450,52 g/L) V.O.C. density at 20 °C: Average carbon number: 8,44 Average molecular weight: 112,53 g/mol With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics: V.O.C. density at 20 °C: 455,16 kg/m³ (455,16 g/L) EU limit for the product (Cat. A.I): 500 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:	
Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	White
Odour:	Characteristic
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	149 °C
Vapour pressure at 20 °C:	560 Pa
Vapour pressure at 50 °C:	3046,2 Pa (3,05 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1400 - 1500 kg/m ³
Relative density at 20 °C:	1,4 - 1,5
Dynamic viscosity at 20 °C:	150 - 250 cP
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm²/s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
*Not relevant due to the nature of the product, not providing i	nformation property of its hazards.

Printing: 28/07/2022 (Replaced 19)

Date of compilation: 15/01/2013



IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)
	Solubility properties:	Insoluble in water
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	31 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	204 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard clas	sses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing info	prmation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Titanium dioxide (2B); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3); Xylene (3);

Ethylbenzene (2B); Toluene (3); Hydrocarbons, C9, aromatics (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200 -753-7 (3); Cobalt bis(2-ethylhexanoate) (2B); Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Talc (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:





SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Δ	cute toxicity	Genus
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	LD50 oral	2100 mg/kg	Rat
CAS: 64742-95-6	LD50 dermal	2000 mg/kg	Rabbit
EC: 265-199-0	LC50 inhalation	Non-applicable	
Xylene	LD50 oral	3523 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene	LD50 oral	2100 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	1100 mg/kg	Rat
EC: 905-562-9	LC50 inhalation	11 mg/L (ATEi)	
Rosin	LD50 oral	4100 mg/kg	Rat
CAS: 8050-09-7	LD50 dermal	Non-applicable	
EC: 232-475-7	LC50 inhalation	Non-applicable	
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl) amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide)	LD50 oral	5100 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	Non-applicable	
EC: 430-050-2	LC50 inhalation	Non-applicable	
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
2-ethylhexanoic acid, zirconium salt	LD50 oral	2043 mg/kg	Rat
CAS: 22464-99-9	LD50 dermal	Non-applicable	
EC: 245-018-1	LC50 inhalation	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	2595,32 mg/kg (Calculation method)	49,63 %
Inhalation	13,05 mg/L (4 h) (Calculation method)	82,18 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	LC50	>1 - 10 (96 h)		Fish
CAS: 64742-95-6	EC50	>1 - 10 (48 h)		Crustacean
EC: 265-199-0	EC50	>1 - 10 (72 h)		Algae
Reaction mass of ethylbenzene and m-xylene and p-xylene	LC50	>10 - 100 (96 h)		Fish
CAS: Non-applicable	EC50	>10 - 100 (48 h)		Crustacean
EC: 905-562-9	EC50	>10 - 100 (72 h)		Algae
trizinc bis(orthophosphate)	LC50	>0.1 - 1 (96 h)		Fish
CAS: 7779-90-0	EC50	>0.1 - 1 (48 h)		Crustacean
EC: 231-944-3	EC50	>0.1 - 1 (72 h)		Algae
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Rosin	LC50	150 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 8050-09-7	EC50	238 mg/L (48 h)	Daphnia magna	Crustacean
EC: 232-475-7	EC50	185 mg/L (72 h)	Selenastrum capricornutum	Algae
Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12- Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide/N,N- Ethane-1,2-diylbis(12-hydroxyoctadecanamide)	LC50	>1 - 10 (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 (48 h)		Crustacean
EC: 430-050-2	EC50	>1 - 10 (72 h)		Algae
Toluene	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 108-88-3	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 203-625-9	EC50	Non-applicable		
2-ethylhexanoic acid, zirconium salt	LC50	270 mg/L (96 h)	N/A	Fish
CAS: 22464-99-9	EC50	Non-applicable		
EC: 245-018-1	EC50	Non-applicable		
Cobalt bis(2-ethylhexanoate)	LC50	>0.1 - 1 (96 h)		Fish
CAS: 136-52-7	EC50	>0.1 - 1 (48 h)		Crustacean
EC: 205-250-6	EC50	>0.1 - 1 (72 h)		Algae
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae





SECTION 12: ECOLOGICAL INFORMATION (continued)

Chronic toxicity:

Identification		Concentration	Species	Genus
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Reaction mass of ethylbenzene and m-xylene and p-xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: Non-applicable EC: 905-562-9	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene	NOEC	Non-applicable		
CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
2-ethylhexanoic acid, zirconium salt	NOEC	Non-applicable		
CAS: 22464-99-9 EC: 245-018-1	NOEC	25 mg/L	Daphnia magna	Crustacean
Cobalt bis(2-ethylhexanoate)	NOEC	0,21 mg/L	Pimephales promelas	Fish
CAS: 136-52-7 EC: 205-250-6	NOEC	0,1697 mg/L	Aeolosoma sp.	Crustacean

12.2 Persistence and degradability:

Identification	Deg	gradability	Biode	egradability
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200 -753-7	BOD5	0,19 g O2/g	Concentration	Non-applicable
CAS: 64742-95-6	COD	0,44 g O2/g	Period	Non-applicable
EC: 265-199-0	BOD5/COD	0,43	% Biodegradable	Non-applicable
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
Reaction mass of ethylbenzene and m-xylene and p-xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: Non-applicable	COD	Non-applicable	Period	28 days
EC: 905-562-9	BOD5/COD	Non-applicable	% Biodegradable	88 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Rosin	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 8050-09-7	COD	Non-applicable	Period	28 days
EC: 232-475-7	BOD5/COD	Non-applicable	% Biodegradable	32 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-ethylhexanoic acid, zirconium salt	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 22464-99-9	COD	Non-applicable	Period	28 days
EC: 245-018-1	BOD5/COD	Non-applicable	% Biodegradable	99 %





SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradab	ility
2-(2-butoxyethoxy)ethanol	BOD5	0,25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2,08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0,12	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7	BCF		
CAS: 64742-95-6	Pow Log	4	
EC: 265-199-0	Potential		
Xylene	BCF	9	
CAS: 1330-20-7	Pow Log	2.77	
EC: 215-535-7	Potential	Low	
Reaction mass of ethylbenzene and m-xylene and p-xylene	BCF	9	
CAS: Non-applicable	Pow Log	2.77	
EC: 905-562-9	Potential	Low	
Ethylbenzene	BCF	1	
CAS: 100-41-4	Pow Log	3.15	
EC: 202-849-4	Potential	Low	
Toluene	BCF	90	
CAS: 108-88-3	Pow Log	2.73	
EC: 203-625-9	Potential	Moderate	
2-ethylhexanoic acid, zirconium salt	BCF		
CAS: 22464-99-9	Pow Log	2.96	
EC: 245-018-1	Potential		
2-(2-butoxyethoxy)ethanol	BCF	0.46	
CAS: 112-34-5	Pow Log	0.56	
EC: 203-961-6	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m ³ /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Reaction mass of ethylbenzene and m-xylene and p-xylene	Кос	202	Henry	524,86 Pa·m³/mol
CAS: Non-applicable	Conclusion	Moderate	Dry soil	Yes
EC: 905-562-9	Surface tension	Non-applicable	Moist soil	Yes





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorp	Absorption/desorption		Volatility	
Ethylbenzene	Кос	520	Henry	798,44 Pa·m³/mol	
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes	
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes	
Toluene	Кос	178	Henry	672,8 Pa·m³/mol	
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes	
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes	
2-ethylhexanoic acid, zirconium salt	Кос	Non-applicable	Henry	2,94E-1 Pa·m ³ /mol	
CAS: 22464-99-9	Conclusion	Non-applicable	Dry soil	Yes	
EC: 245-018-1	Surface tension	Non-applicable	Moist soil	Yes	
2-(2-butoxyethoxy)ethanol	Кос	48	Henry	7,2E-9 Pa·m ³ /mol	
CAS: 112-34-5	Conclusion	Very High	Dry soil	No	
EC: 203-961-6	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No	

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class (Regulation (EU) No 1357/2014)
Г	08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

Date of compilation: 15/01/2013

- CONTINUED ON NEXT PAGE -





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

SECTION 14: TRANSP	ORT	INFORMATION (continued)	
	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
		Labels:	3
		Packing group:	III
		Environmental hazards:	Yes
	14.0	Special precautions for user	162 267 650
		Special regulations: Tunnel restriction code:	163, 367, 650 D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk	Non-applicable
		according to IMO instruments:	
Transport of da	ngero	us goods by sea:	
With regard to IM	1DG 40	-20:	
	14.1	UN number or ID number:	UN1263
	14.2	UN proper shipping name:	PAINT
		Transport hazard class(es):	3
		Labels:	3
	14.4	Packing group:	III
		Marine pollutant:	Yes
	14.6	Special precautions for user	
		Special regulations:	223, 955, 163, 367
		EmS Codes:	F-E, S-E
		Physico-Chemical properties: Limited quantities:	see section 9 5 L
		Segregation group:	Non-applicable
	14 7	Maritime transport in bulk	Non-applicable
	1.117	according to IMO	
		instruments:	
-	-	us goods by air:	
With regard to IA			
		UN number or ID number:	UN1263
		UN proper shipping name:	PAINT
	14.3	Transport hazard class(es):	3
	1 4 4	Labels:	3
		Packing group: Environmental hazards:	III Yes
	-	Special precautions for user	
	1110	Physico-Chemical properties:	see section 9
	14.7	Maritime transport in bulk	Non-applicable
		according to IMO	· · · · · · · · · · · · · · · · · · ·
		instruments:	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -





SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): Supplementary information

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H411: Toxic to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H226: Flammable liquid and vapour. Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Date of compilation: 15/01/2013

- CONTINUED ON NEXT PAGE -





IMPRIMACION MULTISOPORTE BLANCA - Código - 27040

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 1B: H360 - May damage fertility or the unborn child.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

SECTION 16: OTHER INFORMATION (continued) Acute Tox. 4: H302 - Harmful if swallowed.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method Aquatic Chronic 2: Calculation method Skin Sens. 1A: Calculation method Acute Tox. 4: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Dose 50 LC50: Effective concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified. - END OF SAFETY DATA SHEET -