



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

BARNIZ YATES - Código - 42036

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Varnish

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A. Barrio Sakoni, 10 48950 ERANDIO - Vizcaya - España Phone: +34 944 670 062 - Fax: +34 944 675 832 laboratorio@juno.es www.iuno.es

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Sens. 1A: H317 - May cause an allergic skin reaction. STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

Substances that contribute to the classification

Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (CAS: 64742-48-9); 1-methoxy-2-propanol (CAS: 107-98-2); Cobalt bis(2-ethylhexanoate) (CAS: 136-52-7)

UFI: YK80-H09P-200X-Y9V3

** Changes with regards to the previous version





SECTION 2: HAZARDS IDENTIFICATION ** (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | | | | | a |
|--|---|---|---|-------------------------------------|---------------|
| | Identification | | Chemical name/Classification | | Concentration |
| CAS: EC: | 64742-48-9 265-150-3 | Naphtha (petroleum |), hydrotreated heavy, < 0.1 % EC 200-753-7 ⁽¹⁾ | ATP ATP01 | |
| Index: 649-327-00-6 REACH: 01-2119486659-16- XXXX | | Regulation 1272/2008 | Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger | () () () | 10 - <25 % |
| CAS: | 64742-48-9 | Naphtha (petroleum |), hydrotreated heavy, < 0.1 % EC 200-753-7(1) | ATP ATP01 | |
| | 265-150-3 649-327-00-6 01-2119486659-16- XXXX | Regulation 1272/2008 | Asp. Tox. 1: H304; EUH066 - Danger | \$ | 10 - <25 % |
| CAS: | 107-98-2 | 1-methoxy-2-propa | nol ⁽¹⁾ | ATP ATP01 | |
| EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-3 XXXX | 603-064-00-3 01-2119457435-35- | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336 - Warning | >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>> | 1 - <10 % |
| CAS: | 41556-26-7 | Bis(1,2,2,6,6-pentar | nethyl-4-piperidyl) sebacate ⁽¹⁾ | Self-classified | |
| EC: 255-437-1 Index: Non-applicable REACH: Non-applicable | | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning | <u>(1)</u> | 0,1 - <1 % |
| CAS: | 2457-01-4 | Barium bis(2-ethylh | exanoate) ⁽¹⁾ | Self-classified | |
| EC: 219-535-8 Index: Non-applicable REACH: 01-2119983179-22- XXXX | Regulation 1272/2008 | Eye Dam. 1: H318; Repr. 2: H361d - Danger | | 0,1 - <1 % | |
| CAS: | 82919-37-7 | Methyl 1,2,2,6,6-per | ntamethyl-4-piperidyl sebacate ⁽¹⁾ | Self-classified | |
| Index: | EC: 280-060-4 Index: Non-applicable REACH: Non-applicable | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning | <u>(1)</u> | 0,1 - <1 % |
| CAS: | 34590-94-8 | Dipropylene Glycol | Methyl Ether ⁽²⁾ | Not classified | |
| EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60- XXXX | Non-applicable | Regulation 1272/2008 | | | 0,1 - <1 % |
| CAS: | 136-52-7 | Cobalt bis(2-ethylhe | exanoate) ⁽¹⁾ | Self-classified | |
| | 205-250-6 Non-applicable 01-2119524678-29- XXXX | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger | () 🗞 😩 | 0,1 - <1 % |
| CAS: | 136-53-8 | Zinc bis(2-ethylhexa | noate) ⁽¹⁾ | Self-classified | |
| EC: 205-251-1 Index: Non-applicable REACH: 01-2119979071-36- XXXX | | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 2: H36 - Warning | 1d 🕐 🏷 🗞 | 0,1 - <1 % |
| CAS: | 22464-99-9 | 2-ethylhexanoic acid | d, zirconium salt ⁽¹⁾ | Self-classified | |
| | 245-018-1 Non-applicable 01-2119979088-21- XXXX | Regulation 1272/2008 | Repr. 2: H361d - Warning | \$ | 0,1 - <1 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -





SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

| | Identification | Chemical name/Classification | | | |
|--|--|---|--|-----------------|--------|
| CAS: 55406-53-6 | | 3-iodo-2-propynyl Butylcarbamate ⁽¹⁾ ATP ATP06 | | | |
| | 259-627-5 616-212-00-7 01-2120762115-60- XXXX | Regulation 1272/2008 | Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger | | <0,1 % |
| | 108-65-6 | 2-methoxy-1-methy | lethyl acetate ⁽²⁾ | Self-classified | |
| EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29- XXXX | | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336 - Warning | | <0,1 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | | M-factor | | |
|-----------------------|-------------|----------|---------|----|
| 3-iodo-2-propynyl But | /lcarbamate | | Acute | 10 |
| CAS: 55406-53-6 | | | Chronic | 1 |

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

- CONTINUED ON NEXT PAGE -

Date of compilation: 21/01/2013





SECTION 5: FIREFIGHTING MEASURES (continued)

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

- CONTINUED ON NEXT PAGE -





SECTION 7: HANDLING AND STORAGE (continued)

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|---------------------------------|------------------------------|---------|-----------------------|
| 1-methoxy-2-propanol | IOELV (8h) | 100 ppm | 375 mg/m ³ |
| CAS: 107-98-2 EC: 203-539-1 | IOELV (STEL) | 150 ppm | 568 mg/m ³ |
| Dipropylene Glycol Methyl Ether | IOELV (8h) | 50 ppm | 308 mg/m ³ |
| CAS: 34590-94-8 EC: 252-104-2 | IOELV (STEL) | | |
| 2-methoxy-1-methylethyl acetate | IOELV (8h) | 50 ppm | 275 mg/m ³ |
| CAS: 108-65-6 EC: 203-603-9 | IOELV (STEL) | 100 ppm | 550 mg/m ³ |

DNEL (Workers):

| | | Short | exposure | Long | exposure |
|--|------------|--------------------------|---------------------------|-------------------------|--------------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 64742-48-9 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 265-150-3 | Inhalation | 1286,4 mg/m ³ | 1066,67 mg/m ³ | Non-applicable | 837,5 mg/m ³ |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 64742-48-9 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 265-150-3 | Inhalation | 1286,4 mg/m ³ | 1066,67 mg/m ³ | Non-applicable | 837,5 mg/m ³ |
| 1-methoxy-2-propanol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 107-98-2 | Dermal | Non-applicable | Non-applicable | 183 mg/kg | Non-applicable |
| EC: 203-539-1 | Inhalation | 553,5 mg/m ³ | 553,5 mg/m ³ | 369 mg/m ³ | Non-applicable |
| Barium bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 2457-01-4 | Dermal | Non-applicable | Non-applicable | 7,25 mg/kg | Non-applicable |
| EC: 219-535-8 | Inhalation | Non-applicable | Non-applicable | 20,49 mg/m ³ | Non-applicable |
| Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 82919-37-7 | Dermal | Non-applicable | Non-applicable | 0,5 mg/kg | Non-applicable |
| EC: 280-060-4 | Inhalation | Non-applicable | Non-applicable | 0,68 mg/m ³ | Non-applicable |
| Dipropylene Glycol Methyl Ether | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 34590-94-8 | Dermal | Non-applicable | Non-applicable | 283 mg/kg | Non-applicable |
| EC: 252-104-2 | Inhalation | Non-applicable | Non-applicable | 308 mg/m ³ | Non-applicable |
| Cobalt bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 136-52-7 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 205-250-6 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 0,2351 mg/m ³ |

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | | Short | exposure | Long | exposure |
|--------------------------------------|------------|------------------------|------------------------|-------------------------|------------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Zinc bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 136-53-8 | Dermal | Non-applicable | Non-applicable | 2,46 mg/kg | Non-applicable |
| EC: 205-251-1 | Inhalation | Non-applicable | Non-applicable | 17,33 mg/m ³ | Non-applicable |
| 2-ethylhexanoic acid, zirconium salt | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 22464-99-9 | Dermal | Non-applicable | Non-applicable | 6,49 mg/kg | Non-applicable |
| EC: 245-018-1 | Inhalation | Non-applicable | Non-applicable | 32,97 mg/m ³ | Non-applicable |
| 3-iodo-2-propynyl Butylcarbamate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 55406-53-6 | Dermal | Non-applicable | Non-applicable | 2 mg/kg | Non-applicable |
| EC: 259-627-5 | Inhalation | 0,07 mg/m ³ | 1,16 mg/m ³ | 0,023 mg/m ³ | 1,16 mg/m ³ |
| 2-methoxy-1-methylethyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 108-65-6 | Dermal | Non-applicable | Non-applicable | 796 mg/kg | Non-applicable |
| EC: 203-603-9 | Inhalation | Non-applicable | 550 mg/m ³ | 275 mg/m ³ | Non-applicable |

DNEL (General population):

| | | Short | exposure | Long | exposure |
|---|------------|------------------------|-----------------------|------------------------|--------------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 64742-48-9 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 265-150-3 | Inhalation | 1152 mg/m ³ | 640 mg/m ³ | Non-applicable | 178,57 mg/m ³ |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 64742-48-9 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 265-150-3 | Inhalation | 1152 mg/m ³ | 640 mg/m ³ | Non-applicable | 178,57 mg/m ³ |
| I-methoxy-2-propanol | Oral | Non-applicable | Non-applicable | 33 mg/kg | Non-applicable |
| CAS: 107-98-2 | Dermal | Non-applicable | Non-applicable | 78 mg/kg | Non-applicable |
| EC: 203-539-1 | Inhalation | Non-applicable | Non-applicable | 43,9 mg/m ³ | Non-applicable |
| Barium bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | 3,62 mg/kg | Non-applicable |
| CAS: 2457-01-4 | Dermal | Non-applicable | Non-applicable | 3,62 mg/kg | Non-applicable |
| EC: 219-535-8 | Inhalation | Non-applicable | Non-applicable | 6,06 mg/m ³ | Non-applicable |
| Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Oral | Non-applicable | Non-applicable | 0,05 mg/kg | Non-applicable |
| CAS: 82919-37-7 | Dermal | Non-applicable | Non-applicable | 0,25 mg/kg | Non-applicable |
| EC: 280-060-4 | Inhalation | Non-applicable | Non-applicable | 0,17 mg/m ³ | Non-applicable |
| Dipropylene Glycol Methyl Ether | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| CAS: 34590-94-8 | Dermal | Non-applicable | Non-applicable | 121 mg/kg | Non-applicable |
| EC: 252-104-2 | Inhalation | Non-applicable | Non-applicable | 37,2 mg/m ³ | Non-applicable |
| Cobalt bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | 0,175 mg/kg | Non-applicable |
| CAS: 136-52-7 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 205-250-6 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 0,037 mg/m ³ |
| Zinc bis(2-ethylhexanoate) | Oral | Non-applicable | Non-applicable | 1,23 mg/kg | Non-applicable |
| CAS: 136-53-8 | Dermal | Non-applicable | Non-applicable | 1,23 mg/kg | Non-applicable |
| EC: 205-251-1 | Inhalation | Non-applicable | Non-applicable | 4,27 mg/m ³ | Non-applicable |
| 2-ethylhexanoic acid, zirconium salt | Oral | Non-applicable | Non-applicable | 4,51 mg/kg | Non-applicable |
| CAS: 22464-99-9 | Dermal | Non-applicable | Non-applicable | 3,25 mg/kg | Non-applicable |
| EC: 245-018-1 | Inhalation | Non-applicable | Non-applicable | 8,13 mg/m ³ | Non-applicable |
| 2-methoxy-1-methylethyl acetate | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| CAS: 108-65-6 | Dermal | Non-applicable | Non-applicable | 320 mg/kg | Non-applicable |
| EC: 203-603-9 | Inhalation | Non-applicable | Non-applicable | 33 mg/m ³ | 33 mg/m ³ |

- CONTINUED ON NEXT PAGE -





BARNIZ YATES - Código - 42036

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|---|--------------|----------------|-------------------------|--------------|
| 1-methoxy-2-propanol | STP | 100 mg/L | Fresh water | 10 mg/L |
| CAS: 107-98-2 | Soil | 4,59 mg/kg | Marine water | 1 mg/L |
| EC: 203-539-1 | Intermittent | 100 mg/L | Sediment (Fresh water) | 52,3 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 5,2 mg/kg |
| Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | STP | 1 mg/L | Fresh water | 0,002 mg/L |
| CAS: 82919-37-7 | Soil | 0,21 mg/kg | Marine water | 0 mg/L |
| EC: 280-060-4 | Intermittent | 0,009 mg/L | Sediment (Fresh water) | 1,05 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,11 mg/kg |
| Dipropylene Glycol Methyl Ether | STP | 4168 mg/L | Fresh water | 19 mg/L |
| CAS: 34590-94-8 | Soil | 2,74 mg/kg | Marine water | 1,9 mg/L |
| EC: 252-104-2 | Intermittent | 190 mg/L | Sediment (Fresh water) | 70,2 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 7,02 mg/kg |
| Cobalt bis(2-ethylhexanoate) | STP | 0,37 mg/L | Fresh water | 0,00062 mg/L |
| CAS: 136-52-7 | Soil | 10,9 mg/kg | Marine water | 0,00236 mg/L |
| EC: 205-250-6 | Intermittent | Non-applicable | Sediment (Fresh water) | 53,8 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 69,8 mg/kg |
| Zinc bis(2-ethylhexanoate) | STP | 0,53763 mg/L | Fresh water | 0,11075 mg/L |
| CAS: 136-53-8 | Soil | 1,3 mg/kg | Marine water | 0,0328 mg/L |
| EC: 205-251-1 | Intermittent | Non-applicable | Sediment (Fresh water) | 7,83 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,78 mg/kg |
| 3-iodo-2-propynyl Butylcarbamate | STP | 0,44 mg/L | Fresh water | 0,001 mg/L |
| CAS: 55406-53-6 | Soil | 0,005 mg/kg | Marine water | 0 mg/L |
| EC: 259-627-5 | Intermittent | 0,001 mg/L | Sediment (Fresh water) | 0,017 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,002 mg/kg |
| 2-methoxy-1-methylethyl acetate | STP | 100 mg/L | Fresh water | 0,635 mg/L |
| CAS: 108-65-6 | Soil | 0,29 mg/kg | Marine water | 0,064 mg/L |
| EC: 203-603-9 | Intermittent | 6,35 mg/L | Sediment (Fresh water) | 3,29 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,329 mg/kg |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|-----------|---|---|
| Mandatory respiratory tract protection | Filter mask for gases, vapours and particles | | EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998 | Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected. |
| Specific protection | n for the hands | | | |
| Pictogram | PPE | Labelling | CEN Standard | Remarks |
| | | | | |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

JUNO

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



BARNIZ YATES - Código - 42036

| SECTION | 8: EXPOSURE | CONTROLS/PERSON/ | AL PROTECT | ION (continued) | |
|---------|---------------------------------------|--|------------|---|---|
| | | | | | |
| | Pictogram | PPE | Labelling | CEN Standard | Remarks |
| | Mandatory face protection | Face shield | | EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |
| E | Body protection | | | · | - - |
| | Pictogram | PPE | Labelling | CEN Standard | Remarks |
| | Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| | Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | | EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | Evewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| V.O.C. (Supply): | 27,38 % weight |
|---|---|
| V.O.C. density at 20 °C: | 249,18 kg/m³ (249,18 g/L) |
| Average carbon number: | 8,67 |
| Average molecular weight: | 127,78 g/mol |
| With regard to Directive 2004/42/EC, th | is product which is ready to use has the following characteristics: |
| V.O.C. density at 20 °C: | 375,96 kg/m ³ (375,96 g/L) |
| EU limit for the product (Cat. A.E): | 400 g/L (2010) |
| Components: | Non-applicable |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| 9.1 | Information on basic physical and chemical properties: | | | | | |
|-----|--|--|--|--|--|--|
| | For complete information see the product datasheet. | | | | | |
| | Appearance: | | | | | |
| | Physical state at 20 °C: | Liquid | | | | |
| | Appearance: | Viscous | | | | |
| | Colour: | Yellowish | | | | |
| | Odour: | Characteristic | | | | |
| | Odour threshold: | Non-applicable * | | | | |
| | *Not relevant due to the nature of the product, i | not providing information property of its hazards. | | | | |

- CONTINUED ON NEXT PAGE -





SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | Volatility: | |
|----|--|---------------------------------|
| | Boiling point at atmospheric pressure: | 166 °C |
| | Vapour pressure at 20 °C: | 425 Pa |
| | Vapour pressure at 50 °C: | 2365,57 Pa (2,37 kPa) |
| | Evaporation rate at 20 °C: | Non-applicable * |
| | Product description: | |
| | Density at 20 °C: | 860 - 960 kg/m³ |
| | Relative density at 20 °C: | Non-applicable * |
| | Dynamic viscosity at 20 °C: | 15 - 25 cP |
| | Kinematic viscosity at 20 °C: | Non-applicable * |
| | Kinematic viscosity at 40 °C: | >20,5 mm²/s |
| | Concentration: | Non-applicable * |
| | pH: | Non-applicable * |
| | Vapour density at 20 °C: | Non-applicable * |
| | Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| | Solubility in water at 20 °C: | Non-applicable * |
| | Solubility properties: | Soluble in organic solvents |
| | Decomposition temperature: | Non-applicable * |
| | Melting point/freezing point: | Non-applicable * |
| | Flammability: | |
| | Flash Point: | 29 °C |
| | Flammability (solid, gas): | Non-applicable * |
| | Autoignition temperature: | 200 °C |
| | Lower flammability limit: | Not available |
| | Upper flammability limit: | Not available |
| | Particle characteristics: | |
| | Median equivalent diameter: | Non-applicable |
| .2 | Other information: | |
| | Information with regard to physical hazard class | es: |
| | Explosive properties: | Non-applicable * |
| | Oxidising properties: | Non-applicable * |
| | Corrosive to metals: | Non-applicable * |
| | Heat of combustion: | Non-applicable * |
| | Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |
| | Other safety characteristics: | |
| | Surface tension at 20 °C: | Non-applicable * |
| | Refraction index: | Non-applicable * |
| | *Not relevant due to the nature of the product, not providing inform | nation property of its hazards. |

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

9.

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

- CONTINUED ON NEXT PAGE -





SECTION 10: STABILITY AND REACTIVITY (continued)

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

10.5

Applicable for handling and storage at room temperature:

| | Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity | |
|---|------------------------|------------------|-------------------------|-----------------------|----------------|--|
| | Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable | |
| 5 | Incompatible materials | | | | | |
| | | | | | | |
| | Acids | Water | Oxidising materials | Combustible materials | Others | |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):


- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200-753-7 (3); Diiron trioxide (3); Naphtha (petroleum), hydrodesulphurized heavy (3); Naphtha (petroleum), hydrodesulphurized heavy (3); Cobalt bis(2-ethylhexanoate) (2B)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:

** Changes with regards to the previous version







SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Д | cute toxicity | Genus |
|---|-----------------|----------------|--------|
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | LD50 oral | 15000 mg/kg | Rat |
| CAS: 64742-48-9 | LD50 dermal | 3160 mg/kg | Rabbit |
| EC: 265-150-3 | LC50 inhalation | Non-applicable | |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | LD50 oral | 15000 mg/kg | Rat |
| CAS: 64742-48-9 | LD50 dermal | 3160 mg/kg | Rabbit |
| EC: 265-150-3 | LC50 inhalation | Non-applicable | |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | LD50 oral | 2615 mg/kg | Rat |
| CAS: 41556-26-7 | LD50 dermal | Non-applicable | |
| EC: 255-437-1 | LC50 inhalation | Non-applicable | |
| Dipropylene Glycol Methyl Ether | LD50 oral | >5000 mg/kg | Rat |
| CAS: 34590-94-8 | LD50 dermal | 9510 mg/kg | Rabbit |
| EC: 252-104-2 | LC50 inhalation | Non-applicable | |
| Zinc bis(2-ethylhexanoate) | LD50 oral | 2043 mg/kg | Rat |
| CAS: 136-53-8 | LD50 dermal | Non-applicable | |
| EC: 205-251-1 | LC50 inhalation | Non-applicable | |
| 2-ethylhexanoic acid, zirconium salt | LD50 oral | 2043 mg/kg | Rat |
| CAS: 22464-99-9 | LD50 dermal | Non-applicable | |
| EC: 245-018-1 | LC50 inhalation | Non-applicable | |
| 3-iodo-2-propynyl Butylcarbamate | LD50 oral | 1100 mg/kg | Rat |
| CAS: 55406-53-6 | LD50 dermal | 2100 mg/kg | Rabbit |
| EC: 259-627-5 | LC50 inhalation | Non-applicable | |
| 2-methoxy-1-methylethyl acetate | LD50 oral | 8532 mg/kg | Rat |
| CAS: 108-65-6 | LD50 dermal | >5000 mg/kg | Rat |
| EC: 203-603-9 | LC50 inhalation | 30 mg/L (4 h) | Rat |

Acute Toxicity Estimate (ATE mix):

| ATE mix | | Ingredient(s) of unknown toxicity |
|------------|-------------------------------------|-----------------------------------|
| Oral | >2000 mg/kg (Calculation method) | Non-applicable |
| Dermal | >2000 mg/kg (Calculation method) | Non-applicable |
| Inhalation | >20 mg/L (4 h) (Calculation method) | Non-applicable |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -





SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | | Concentration | Species | Genus |
|---|------|-------------------|---------------------------|------------|
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | LC50 | 2200 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 64742-48-9 | EC50 | 1000 mg/L (96 h) | Daphnia magna | Crustacean |
| EC: 265-150-3 | EC50 | Non-applicable | | |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | LC50 | 2200 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 64742-48-9 | EC50 | 1000 mg/L (96 h) | Daphnia magna | Crustacear |
| EC: 265-150-3 | EC50 | Non-applicable | | |
| 1-methoxy-2-propanol | LC50 | 20800 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 107-98-2 | EC50 | 23300 mg/L (48 h) | Daphnia magna | Crustacear |
| EC: 203-539-1 | EC50 | 1000 mg/L (168 h) | Selenastrum capricornutum | Algae |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | LC50 | 0,97 mg/L (96 h) | Lepomis macrochirus | Fish |
| CAS: 41556-26-7 | EC50 | 20 mg/L (24 h) | Daphnia magna | Crustacear |
| EC: 255-437-1 | EC50 | Non-applicable | | |
| Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | LC50 | >0.1 - 1 (96 h) | | Fish |
| CAS: 82919-37-7 | EC50 | >0.1 - 1 (48 h) | | Crustacear |
| EC: 280-060-4 | EC50 | >0.1 - 1 (72 h) | | Algae |
| Dipropylene Glycol Methyl Ether | LC50 | 10000 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 34590-94-8 | EC50 | 1919 mg/L (48 h) | Daphnia magna | Crustacear |
| EC: 252-104-2 | EC50 | Non-applicable | | |
| Cobalt bis(2-ethylhexanoate) | LC50 | >0.1 - 1 (96 h) | | Fish |
| CAS: 136-52-7 | EC50 | >0.1 - 1 (48 h) | | Crustacear |
| EC: 205-250-6 | EC50 | >0.1 - 1 (72 h) | | Algae |

** Changes with regards to the previous version





BARNIZ YATES - Código - 42036

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | | Concentration | Species | Gen |
|---|------|------------------|-------------------------|--------|
| Zinc bis(2-ethylhexanoate) | LC50 | 107 mg/L (96 h) | N/A | Fis |
| CAS: 136-53-8 | EC50 | 16 mg/L (48 h) | Daphnia magna | Crusta |
| EC: 205-251-1 | EC50 | Non-applicable | | |
| 2-ethylhexanoic acid, zirconium salt | LC50 | 270 mg/L (96 h) | N/A | Fis |
| CAS: 22464-99-9 | EC50 | Non-applicable | | |
| EC: 245-018-1 | EC50 | Non-applicable | | |
| 3-iodo-2-propynyl Butylcarbamate | LC50 | 0,07 mg/L (96 h) | Oncorhynchus mykiss | Fis |
| CAS: 55406-53-6 | EC50 | 0,09 mg/L (96 h) | Mysidopsis bahia | Crusta |
| EC: 259-627-5 | EC50 | 0,05 mg/L (72 h) | Scenedesmus subspicatus | Alga |
| 2-methoxy-1-methylethyl acetate | LC50 | 161 mg/L (96 h) | Pimephales promelas | Fis |
| CAS: 108-65-6 | EC50 | 481 mg/L (48 h) | Daphnia sp. | Crusta |
| EC: 203-603-9 | EC50 | Non-applicable | | |
| Chronic toxicity: | | | | |
| Identification | | Concentration | Species | Gen |
| Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | NOEC | Non-applicable | | |
| CAS: 82919-37-7 EC: 280-060-4 | NOEC | 1 mg/L | Daphnia magna | Crusta |
| Dipropylene Glycol Methyl Ether | NOEC | Non-applicable | | |
| CAS: 34590-94-8 EC: 252-104-2 | NOEC | 0,5 mg/L | Daphnia magna | Crusta |
| Cobalt bis(2-ethylhexanoate) | NOEC | 0,21 mg/L | Pimephales promelas | Fis |
| CAS: 136-52-7 EC: 205-250-6 | NOEC | 0,1697 mg/L | Aeolosoma sp. | Crusta |
| Zinc bis(2-ethylhexanoate) | NOEC | 0,025 mg/L | Clupea harengus | Fis |
| CAS: 136-53-8 EC: 205-251-1 | NOEC | 0,101 mg/L | Americamysis bahia | Crusta |
| 2-ethylhexanoic acid, zirconium salt | NOEC | Non-applicable | | |
| CAS: 22464-99-9 EC: 245-018-1 | NOEC | 25 mg/L | Daphnia magna | Crusta |
| 3-iodo-2-propynyl Butylcarbamate | NOEC | 0,0084 mg/L | Pimephales promelas | Fis |
| CAS: 55406-53-6 EC: 259-627-5 | NOEC | 0,0499 mg/L | Daphnia magna | Crusta |
| 2-methoxy-1-methylethyl acetate | NOEC | 47,5 mg/L | Oryzias latipes | Fis |
| CAS: 108-65-6 EC: 203-603-9 | NOEC | 100 mg/L | Daphnia magna | Crusta |

** Changes with regards to the previous version





BARNIZ YATES - Código - 42036

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | De | egradability | Biode | egradability |
|--|----------|----------------|-----------------|----------------|
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 64742-48-9 | COD | Non-applicable | Period | 28 days |
| EC: 265-150-3 | BOD5/COD | Non-applicable | % Biodegradable | 89,9 % |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 64742-48-9 | COD | Non-applicable | Period | 28 days |
| EC: 265-150-3 | BOD5/COD | Non-applicable | % Biodegradable | 89,9 % |
| 1-methoxy-2-propanol | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 107-98-2 | COD | Non-applicable | Period | 28 days |
| EC: 203-539-1 | BOD5/COD | Non-applicable | % Biodegradable | 90 % |
| Dipropylene Glycol Methyl Ether | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 34590-94-8 | COD | 0 g O2/g | Period | 28 days |
| EC: 252-104-2 | BOD5/COD | Non-applicable | % Biodegradable | 73 % |
| Zinc bis(2-ethylhexanoate) | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 136-53-8 | COD | Non-applicable | Period | 28 days |
| EC: 205-251-1 | BOD5/COD | Non-applicable | % Biodegradable | 60 % |
| 2-ethylhexanoic acid, zirconium salt | BOD5 | Non-applicable | Concentration | 20 mg/L |
| CAS: 22464-99-9 | COD | Non-applicable | Period | 28 days |
| EC: 245-018-1 | BOD5/COD | Non-applicable | % Biodegradable | 99 % |
| 2-methoxy-1-methylethyl acetate | BOD5 | Non-applicable | Concentration | 785 mg/L |
| CAS: 108-65-6 | COD | Non-applicable | Period | 8 days |
| EC: 203-603-9 | BOD5/COD | Non-applicable | % Biodegradable | 100 % |

12.3 Bioaccumulative potential:

| Identification | | Bioaccumulation potential | |
|--------------------------------------|-----------|---------------------------|--|
| 1-methoxy-2-propanol | BCF | 3 | |
| CAS: 107-98-2 | Pow Log | -0.44 | |
| EC: 203-539-1 | Potential | Low | |
| Dipropylene Glycol Methyl Ether | BCF | 1 | |
| CAS: 34590-94-8 | Pow Log | -0.06 | |
| EC: 252-104-2 | Potential | Low | |
| 2-ethylhexanoic acid, zirconium salt | BCF | | |
| CAS: 22464-99-9 | Pow Log | 2.96 | |
| EC: 245-018-1 | Potential | | |

** Changes with regards to the previous version



BARNIZ YATES - Código - 42036



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | | Bioaccumulation potential | |
|----------------------------------|-----------|---------------------------|--|
| 3-iodo-2-propynyl Butylcarbamate | BCF | 36 | |
| CAS: 55406-53-6 | Pow Log | 2.4 | |
| EC: 259-627-5 | Potential | Moderate | |
| 2-methoxy-1-methylethyl acetate | BCF | 1 | |
| CAS: 108-65-6 | Pow Log | 0.43 | |
| EC: 203-603-9 | Potential | Low | |

12.4 Mobility in soil:

| Identification | Absorp | Absorption/desorption | | Volatility | |
|---|-----------------|-----------------------|------------|--------------------------------|--|
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Кос | 100 | Henry | Non-applicable | |
| CAS: 64742-48-9 | Conclusion | High | Dry soil | Non-applicable | |
| EC: 265-150-3 | Surface tension | Non-applicable | Moist soil | Non-applicable | |
| Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 | Кос | 100 | Henry | Non-applicable | |
| CAS: 64742-48-9 | Conclusion | High | Dry soil | Non-applicable | |
| EC: 265-150-3 | Surface tension | Non-applicable | Moist soil | Non-applicable | |
| 2-ethylhexanoic acid, zirconium salt | Кос | Non-applicable | Henry | 2,94E-1 Pa·m ³ /mol | |
| CAS: 22464-99-9 | Conclusion | Non-applicable | Dry soil | Yes | |
| EC: 245-018-1 | Surface tension | Non-applicable | Moist soil | Yes | |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) | | |
|--|---|---|--|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous | | |
| Type of waste (Regulation (FII) No 1357/2014): | | | | |

Type of waste (Regulation (EU) No 1357/2014):



BARNIZ YATES - Código - 42036



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

| with regard to Ai | DK 202 | | | | | | | |
|--------------------------------------|------------------|---------------------------------------|--------------------|--|--|--|--|--|
| | 14.1 | UN number or ID number: | UN1263 | | | | | |
| | 14.2 | UN proper shipping name: | PAINT | | | | | |
| | 14.3 | Transport hazard class(es): | 3 | | | | | |
| $\langle \simeq \rangle$ | | Labels: | 3 | | | | | |
| | 14.4 | Packing group: | III | | | | | |
| 3 | 14.5 | Environmental hazards: | No | | | | | |
| | 14.6 | Special precautions for user | | | | | | |
| | | Special regulations: | 163, 367, 650 | | | | | |
| | | Tunnel restriction code: | D/E | | | | | |
| | | Physico-Chemical properties: | see section 9 | | | | | |
| | | Limited quantities: | 5 L | | | | | |
| | 14.7 | Maritime transport in bulk | Non-applicable | | | | | |
| | according to IMO | | | | | | | |
| _ | | instruments: | | | | | | |
| Transport of da | ingero | us goods by sea: | | | | | | |
| With regard to IN | 1DG 40 | -20: | | | | | | |
| | 14.1 | UN number or ID number: | UN1263 | | | | | |
| | 14.2 | UN proper shipping name: | PAINT | | | | | |
| | 14.3 | Transport hazard class(es): | 3 | | | | | |
| | | Labels: | 3 | | | | | |
| | 14.4 | Packing group: | III | | | | | |
| 3 | 14.5 | Marine pollutant: | No | | | | | |
| | 14.6 | Special precautions for user | | | | | | |
| | | Special regulations: | 223, 955, 163, 367 | | | | | |
| | | EmS Codes: | F-E, S-E | | | | | |
| | | Physico-Chemical properties: | see section 9 | | | | | |
| | | Limited quantities: | 5 L | | | | | |
| | | Segregation group: | Non-applicable | | | | | |
| | 14.7 | · · · · · · · · · · · · · · · · · · · | Non-applicable | | | | | |
| | | according to IMO | | | | | | |
| | | instruments: | | | | | | |
| Transport of dangerous goods by air: | | | | | | | | |
| With regard to IA | TA/ICA | AO 2022: | | | | | | |
| | | | | | | | | |

- CONTINUED ON NEXT PAGE -L/2013 Revised: 07/04/2022





BARNIZ YATES - Código - 42036

SECTION 14: TRANSPORT INFORMATION (continued)

| 14 14 3 14 | UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: | 3 III |
|---------------------|--|----------------|
| 14 | 5 Environmental hazards: | No |
| 14 | 6 Special precautions for user Physico-Chemical properties: | see section 9 |
| 14 | 7 Maritime transport in bulk according to IMO instruments: | Non-applicable |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 3-iodo-2-propynyl Butylcarbamate.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 3-iodo-2-propynyl Butylcarbamate (Product-type 6, 7, 8, 9, 10, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| | Section | Description | Lower-tier requirements | Upper-tier requirements |
|---|---------|-------------------|----------------------------|----------------------------|
| Г | P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

** Changes with regards to the previous version





SECTION 16: OTHER INFORMATION ** (continued)

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12): New declared substances 3-iodo-2-propynyl Butylcarbamate (55406-53-6) · Removed substances octhilinone (ISO) (26530-20-1) Substances that contribute to the classification (SECTION 2): Removed substances octhilinone (ISO) (26530-20-1) CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): Pictograms · Hazard statements Texts of the legislative phrases mentioned in section 2: H336: May cause drowsiness or dizziness. H317: May cause an allergic skin reaction. H412: Harmful to aquatic life with long lasting effects. H226: Flammable liquid and vapour. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 3: H331 - Toxic if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Dam. 1: H318 - Causes serious eye damage. Eve Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 1B: H360 - May damage fertility or the unborn child. Repr. 2: H361d - Suspected of damaging the unborn child. Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause drowsiness or dizziness. **Classification procedure:** STOT SE 3: Calculation method Skin Sens. 1A: Calculation method Aquatic Chronic 3: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms:

** Changes with regards to the previous version



BARNIZ YATES - Código - 42036



SECTION 16: OTHER INFORMATION ** (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

** Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified. - END OF SAFETY DATA SHEET -