

# Technical Datasheet

## Retardant Thinner D-71 PUR.



Product Code: 50014 Thinners

### DESCRIPTION

Retardant thinner for polyurethane enamels, especially indicated when ambient temperatures are higher than normal, allowing longer open time and improved brushability.

Colour: Clear

Density:  $0,90 \pm 0,05$  g/cc S/FR1002

Flash Point: Flammable (32 °C)

### USE

Used for dilution of polyurethane enamels.

Cleaning of utensils used in the application process.

Use only with coatings where this product is indicated for use in their technical datasheets.

50014 CLEAR



Formato: 1 / 5 / 20 L

### PROPERTIES

- Avoids blistering during drying process of PU coatings.
- Improves leveling
- Provides good brushability.
- Adequate evaporation speed that allows a uniform finish.

### SURFACE PREPARATION

See paint/coating's technical datasheet for indications of recommended use.

### APPLICATION TIPS

**AS THINNER.** Add the recommended amount according to the technical data sheet of the coating product to be diluted. Stir the mixture steadily until complete homogenization.

**FOR CLEANING.** Clean tools immediately after use to prevent paint from drying out. Perfectly remove the remains of paint and then wash the material with soapy water. Let tools dry completely.

### SAFETY AND ENVIRONMENT

The product must be handled only in conditions with good air ventilation and with the necessary protection measures.

Avoid sources of ignition. The vapors it contains should not be inhaled.

Avoid contact with skin and eyes by wearing gloves and protective goggles.

In case of splashes, wash with plenty of water. For more information consult the Safety Data Sheet.

Store the excess material in a ventilated and dry place. Close containers carefully and keep upright to avoid spillage.

Preserve the containers from frost, high temperatures and direct sun exposure.

Do not eat, drink, or smoke during the preparation and application of the product. Keep out of the reach of children.

Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your town hall about the correct recycling of both the container, as well as the waste and leftovers of the product in accordance with the law and principles of environmental respect.

The information contained in this technical sheet may change and must be updated. See [www.juno.es](http://www.juno.es) or your nearest JUNO representative for the latest data sheet.

Technical application advice, whether verbal, in writing or through testing, is based on JUNO's technical knowledge and experience. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, use and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the customer, applicator or handler of the products and not of the supplying company. This document does not exempt the client from carrying out her own examination of the products supplied, in order to verify their suitability for the procedures and purposes foreseen. In the event of liability assumed by JUNO, it will be limited to the strict value of the merchandise supplied and used by the customer, whatever the damages caused.

JUNO guarantees the quality of all its products, in accordance with the General Conditions of Sale in force.  
Industrias JUNO, S.A. • Barrio Sakonli, 10 • 48950 Erandio (Bizkaia) • Tel. +34 944 670 062 • [infoweb@juno.es](mailto:infoweb@juno.es) • [www.junopaints.com](http://www.junopaints.com)

Junio 2018 Rev. 01

1 / 1