

Technical Datasheet

D-75 Retardant thinner

JUNO

Product Code: 50107 Thinners

DESCRIPTION

Retardant thinner for Junolac Anti-oxidant (AO), specifically recommended when painting large surfaces or when ambient temperatures are high, allowing for good brushability.

Colour: Incolore**Density:** 0,88 ± 0,05 g/cc S/FR1002**Flashpoint:** Flammable (75 °C)

USE

Dilution of Junolac Anticorrosive

Cleaning of tools used in the application

Use only with products for which it is recommended in the technical datasheet

50107 CLEAR

PROPERTIES

- Prevents bubble formation
- Improves levelling
- Provides good brushability
- Appropriate evaporation rate allowing a uniform finish



Formato: 1 / 5 L

SURFACE PREPARATION

Proceed as specified in the technical datasheet of the paint for which this product is recommended.

APPLICATION TIPS

AS THINNER. Add the recommended amount as specified in the technical datasheet of the product to be thinned. Stir the mixture slowly until fully homogenised.

FOR CLEANING. Clean tools immediately after use to prevent the paint from drying. Remove all paint residues thoroughly, then wash the equipment with soapy water. Allow tools to dry completely.

OBSERVATIONS:

Adding this solvent extends drying and recoating times.

SAFETY & ENVIRONMENT

The product must be handled in a well-ventilated area and with appropriate protective measures. Avoid sources of ignition. Do not inhale the vapours. Avoid contact with skin and eyes by using gloves and protective goggles. In case of splashes, rinse thoroughly with plenty of water. For further information, consult the Safety Data Sheet.

Store any remaining material in a dry, well-ventilated area. Close containers carefully and keep them upright to prevent spills. Protect containers from frost, high temperatures, and direct sunlight.

Do not eat, drink, or smoke during the preparation and application of the product. Keep out of reach of children.

Do not pour into drains or release into the environment. Dispose of at an authorised waste collection point.

Contact your local council for guidance on the correct recycling of both the container and any waste or leftover product, in accordance with legal requirements and environmental protection principles.

The information contained in this technical datasheet may be subject to change and should be kept up to date. Please consult www.juno.es or your nearest JUNO representative to obtain the most recent version of the technical datasheet. Application advice—whether verbal, written, or based on testing—is based on JUNO's experience and technical knowledge. The data provided in this document should be regarded as a recommendation and does not imply any obligation, including with respect to potential third-party industrial property rights. The application, use, and processing of products supplied by JUNO are carried out by third parties. Consequently, the final result is solely the responsibility of the customer, applicator, or handler of the products, and not of the supplying company. This document does not exempt the customer from carrying out their own assessment of the products supplied, in order to verify their suitability for the intended procedures and purposes. In the event that JUNO accepts liability, such liability shall be strictly limited to the value of the goods supplied and used by the customer, regardless of any damages or losses that may have occurred. JUNO guarantees the quality of all its products in accordance with its current General Conditions of Sale.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (Bizkaia) • Tel. 944 670 062 • infoweb@juno.es • www.juno.es

November 2019 Rev. 00

1 / 1